

BLIND RIVETING TOOL BNW 25 KN BASIC EDITION



□

Description

The pneumatic, hydraulic blind riveting tool is designed for all common riveting rocesses in the thin sheet metall field. Setting blind rivets has never been easier. The rivet head is hold in place by magnetic spots. Choose from many optional accessories to meet your own workflow.

Benefits

- Low weight
- Small compact designed
- Flexible in all directions
- Collection chamber for demolished tension bolts
- Applicable for all blind rivets and rivet nuts on the market

Scope of delivery

- Blind Riveting Adapter incl. Universal Adaption
- Universal Adaption accessorie kit
- Control Unit
- Mounting key
- Case with Inlay
- User Manual

Technical data

Hub	20mm
Setting force	24,5kN on 6 bar
Working pressure, hydraulic	max. 600 bar
Working pressure, pneumatic	6 bar
Ambiente temperature	5 - 50 °C/ 41 - 122 °F
Scoped drive	Hydraulic pump PNP 90

Dimensions & Weight

L x W x H	109 x 37 x 62 mm cm x cm x cm
Weight	0,0 kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH
Im Oberen Tal 31
74858 Aglasterhausen
GERMANY

Tel: +49 (0) 6262 / 92 605-0
Fax: +49 (0) 6262 / 92 605-29
Mail: info@kamatec.com
Web: www.kamatec.com